



TUBI DI RAME PREISOLATI
ISOLAMENTI IN POLIETILENE ESPANSO PER TUBAZIONI

ISOCLIMA S.p.A. 25086 REZZATO (BS) - Via Giovanni XXIII, 58
Tel. 030 2590700 - Fax 030 2590719
Internet address: www.isoclima.com - E-mail: isoclima@isoclima.com
Cap.Soc. € 9.000.000,00 i.v. - C.C.I.A.A. BS 354531 - Reg. Soc. Trib. BS 55484
Cod. Fisc e Partita IVA 03295180172



Rezzato, 17/05/19

Oggetto: ISOPOLAR / BIPOLAR presinsulated copper pipe conformity declaration
Isoclima SPA, accordingly with the following Italian laws:

- DPR N° 1095, 03rd August 1968
- DPR N° 447, 6th December 1991

DECLARES

under its responsibility, that the pre-insulated copper pipe produced with brand ISOPOLAR / BIPOLAR for air conditioning appliances is according with the following requirements:

COPPER PIPE

- Type of copper: CU – DHP 99,9%
- Residual phosphor: between 0,015% and 0,040%
- EN 12735 - 1

INSULATION

- LDPE sheet, closed cell, self extinguish Class 1, M1, EUROCLASS BLS2D0
- Working temperature: -80° C / +98° C
- Coeff. Of water vapour dispersion: 5.482
- Thermal conductivity: 0,0397 W . m-1 . K-1
- Insulation wall thickness according with L. 10/91
- CFC free
- ecological

WORKING PRESSURE

1/4x0,80.....	139 bar
3/8x0,80	93
1/2x0,80	70
5/8x1	69
3/4x1	61
7/8x1	50

The above described product is guaranteed for the gas R407, R410 and R32.
Isoclima releases this certificate for the permitted uses.
The conformity depends on the full respect of the laws in installation.

ISOCLIMA SPA