

TOPENÍ – hodnoty maximálních výkonů vč. efektu odtávání**HU041MR.U20 + HN0613M.NK5 / HN0613T.NK0**

Outdoor Temperature [°C DB]	Water flow rate 11.50 LPM											
	LWT 30 °C		LWT 35 °C		LWT 40 °C		LWT 45 °C		LWT 50 °C		LWT 55 °C	
	TC	COP	TC	COP	TC	COP	TC	COP	TC	COP	TC	COP
-20	4.00	2.48	4.00	2.17	4.00	1.90	4.00	1.80				
-15	4.00	2.63	4.00	2.43	4.00	2.22	4.00	2.06	4.00	1.91		
-7	4.00	3.67	4.00	3.08	4.00	2.82	4.00	2.56	4.00	2.41	4.00	2.22
-4	4.00	4.08	4.00	3.53	4.00	3.10	4.00	2.77	4.00	2.55	4.00	2.44
-2	4.00	4.35	4.00	3.76	4.00	3.28	4.00	2.91	4.00	2.64	4.00	2.48
2	4.00	4.66	4.00	3.63	4.00	3.48	4.00	3.04	4.00	2.70	4.00	2.46
7	4.00	5.63	4.00	5.10	4.00	4.15	4.00	3.57	4.00	3.11	4.00	2.77
10	4.00	6.07	4.00	5.21	4.00	4.46	4.00	3.81	4.00	3.30	4.00	2.89
15	4.00	6.82	4.00	5.84	4.00	4.98	4.00	4.22	4.00	3.57	4.00	3.06
18	4.00	7.28	4.00	6.24	4.00	5.30	4.00	4.48	4.00	3.76	4.00	3.16
20	4.00	7.59	4.00	6.50	4.00	5.52	4.00	4.65	4.00	3.90	4.00	3.43
35	4.00	10.02	4.00	8.59	4.00	7.28	4.00	6.07	4.00	4.97	4.00	3.61

HU061MR.U20 + HN0613M.NK5 / HN0613T.NK0

Outdoor Temperature [°C DB]	Water flow rate 17.25 LPM											
	LWT 30 °C		LWT 35 °C		LWT 40 °C		LWT 45 °C		LWT 50 °C		LWT 55 °C	
	TC	COP	TC	COP	TC	COP	TC	COP	TC	COP	TC	COP
-20	4.92	2.40	4.78	2.10	4.64	1.84	4.50	1.74				
-15	5.56	2.55	5.52	2.35	5.48	2.15	5.44	1.99	5.40	1.85		
-7	6.00	3.55	6.00	2.98	6.00	2.74	6.00	2.48	6.00	2.34	6.00	2.15
-4	6.00	3.95	6.00	3.42	6.00	3.00	6.00	2.68	6.00	2.47	6.00	2.36
-2	6.00	4.21	6.00	3.64	6.00	3.18	6.00	2.82	6.00	2.56	6.00	2.41
2	6.00	4.52	6.00	3.52	6.00	3.37	6.00	2.94	6.00	2.61	6.00	2.39
7	6.00	5.45	6.00	4.95	6.00	4.02	6.00	3.46	6.00	3.01	6.00	2.68
10	6.00	5.88	6.00	5.04	6.00	4.32	6.00	3.69	6.00	3.20	6.00	2.80
15	6.00	6.60	6.00	5.66	6.00	4.82	6.00	4.09	6.00	3.46	6.00	2.96
18	6.00	7.05	6.00	6.04	6.00	5.14	6.00	4.34	6.00	3.65	6.00	3.06
20	6.00	7.35	6.00	6.30	6.00	5.35	6.00	4.51	6.00	3.78	6.00	3.32
35	6.00	9.70	6.00	8.32	6.00	7.05	6.00	5.88	6.00	4.81	6.00	3.50

LWT: Výstupní teplota vody (°C)

COP: poměr výkonu k el. příkonu (kW/kW)

TC: maximální výkon (kW)

Water flow rate: vodní průtok (l/min)

Outdoor temperature (°C DB): Venkovní teplota (°C teplota suchého teploměru)

Postup měření odpovídá EN-14511