

Rekuperační jednotky ERV

Statický externí tlak + množství vzduchu

◆ LZ-H025GBA4

Setting Value	External Static Pressure Pa (in.wg)				
	0 (0.0)	30 (0.1)	50 (0.2)	100 (0.4)	150 (0.6)
	Air Flow Rate [CMH]				
75	261	177	132	18	-
91	353	300	228	18	-
107	425	374	335	250	30

◆ LZ-H035GBA5

Setting Value	External Static Pressure Pa (in.wg)				
	0 (0.0)	30 (0.1)	50 (0.2)	100 (0.4)	150 (0.6)
	Air Flow Rate [CMH]				
75	261	177	132	-	-
91	353	290	240	10	-
107	445	390	350	220	-
125	533	491	455	350	240

◆ LZ-H150GBA5 / LZ-H200GBA5

Setting Value	External Static Pressure Pa (in.wg)							
	0 (0.0)	30 (0.1)	50 (0.2)	100 (0.4)	150 (0.6)	200 (0.8)	250 (1.0)	300 (1.2)
	Air Flow Rate [CMH]							
65	1,172	840	570	34	-	-	-	-
82	1,550	1,372	1,218	698	34	-	-	-
93	1,852	1,662	1,506	1,120	560	220	-	-
105	2,074	1,958	1,878	1,556	1,144	600	40	-
116	2,344	2,254	2,174	1,900	1,576	1,216	510	180
127	2,670	2,564	2,496	2,210	1,944	1,664	1,172	560
133	2,776	2,686	2,598	2,338	2,064	1,766	1,430	600
138	2,882	2,784	2,726	2,574	2,410	1,972	1,766	1,396

Setting value (SV) = nastavená hodnota na dálkovém ovladači

Static Pressure = ext. statický tlak (Pa / palce vodního sloupce)

Hodnoty množství vzduchu jsou uváděny v m³/hod (Air Flow Rate / CMH)

ZE050GUCCA0, ZE080~100GUCCA0

Model	Step	Air Flow [CMH]	External Static Pressure [Pa]															
			0		30		50		70		100		150		200		250	
			RPM															
			SA	EA	SA	EA	SA	EA	SA	EA	SA	EA	SA	EA	SA	EA	SA	EA
ZE050GUCCA0	Low	300	900	800	1,030	930	1,090	1,020	1,160	1,090	1,260	1,200	1,420	1,360	1,550	1,500	-	-
	High	400	1,090	970	1,190	1,090	1,250	1,150	1,320	1,230	1,400	1,320	1,530	1,470	1,640	1,600	-	-
	Super-High	500	1,300	1,140	1,380	1,240	1,430	1,310	1,490	1,380	1,550	1,440	1,680	1,600	-	-	-	-
ZE080GUCCA0	Low	480	650	550	750	650	820	720	870	800	980	900	1,090	1,040	1,200	1,160	1,310	1,280
	High	640	800	650	870	730	930	810	960	870	1,050	960	1,170	1,090	1,260	1,210	1,360	1,310
	Super-High	800	930	770	1,000	850	1,050	910	1,100	970	1,160	1,040	1,250	1,150	1,360	1,260	-	-
ZE100GUCCA0	Low	600	750	620	840	730	910	800	950	850	1,040	940	1,150	1,080	1,260	1,200	1,360	1,310
	High	800	930	770	1,000	850	1,050	910	1,100	970	1,160	1,040	1,250	1,150	1,360	1,260	-	-
	Super-High	1000	1,110	920	1,180	1,000	1,220	1,060	1,260	1,110	1,310	1,160	1,360	1,220	-	-	-	-

SA (Supply air) - přívodní vzduch / EA (Exhaust air) - odvodní vzduch

RPM - otáčky/min

External static Pressure = ext. statický tlak (Pa)

Hodnoty množství vzduchu jsou uváděny v m³/hod (Air Flow / CMH)