

[Unit: mm]

Chassis code : U4

Front View: Dimensions include 165, 620, 330, 360, 390, 26, 950, 24, 834, 330, 24, 32, 24, 330, 292, 277, 112, 40, 416, 696, 250, 91. Callouts A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z.

Side View: Dimensions include 12, 43, 591, 82, 57, 22, 70x4=280, 122, 85, 70x4=280. Callout 1.

Top View: Dimensions include 165, 620, 330, 360, 390, 26, 950, 24, 834, 330, 24, 32, 24, 330, 292, 277, 112, 40, 416, 696, 250, 91. Callouts A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z.

3D View: Shows the chassis from a perspective view.

Note:

- Unit should be installed in compliance with the installation manual in the product box.
- Unit should be grounded in accordance with the local regulations or applicable national codes.
- All electrical components and materials to be supplied from the site must comply with the local regulations or international codes.
- Electric characteristics chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.

Symbols:

- Piping Direction
- Datum line

No.	Part Name	Description
1	Air Outlet	-
2	Power Supply cable Hole	ODU power supply
3	Power and Communication Cable hole	ODU-IDU connection
4	Gas pipe Connection	Flare joint
5	Liquid pipe Connection	Flare joint
6	Handle	-
7	SVC Valve (Gas)	Flare joint
8	SVC Valve (Liquid)	Flare joint